

**THE SINGARENI COLLIERIES COMPANY LIMITED**  
**(A GOVERNMENT COMPANY)**  
**PURCHASE DEPARTMENT, SINGARENI BHAVAN,**  
**RED HILLS, PO: KHAIRTABAD, HYDERABAD – 500004**  
**TELANGANA (STATE)**  
**CIN:U10102TG1920SGC000571**  
**TELEPHONE: 040-23316964 - EPABX: 040-23142 EXTN.224/225**  
**TELE FAX: 040-23307653 ; e-mail ID: pd\_hyd@scclmines.com.**  
**Company Web site: [www.scclmines.com](http://www.scclmines.com)**  
**SCCL GST No : 36AAACT8873F1Z1**  
**NOTICE INVITING TENDERS (NIT)**

**ENQ.NO & DATE: HY124O0078 DT: 08.06.2024**

**DT: 08.06.2024**

**Sub:** Procurement of Audio-Visual equipment to PPD conference hall, Singareni Bhavan, Hyderabad - Reg  
 -oOo-

**ENQ CLOSING DATE: 03.07.2024 ON OR BEFORE 3.00PM**

**ENQ OPENING DATE: 03.07.2024 AFTER 3.00 PM**

MODE OF ENQUIRY : OPEN TENDER  
 NUMBER OF SOURCES : SINGLE  
 MODE OF TENDERING : SINGLE COVER

Sl.No	Item Code	Material Desc.	Qty	Unit
1	5758880115	PEOPLE LINK 12X ELITE CAMERA	1	NOS
2	5758181134	YAMAHA YVC 330 Mic	1	NOS

**Specifications:** Detailed Specifications are attached.

**ONLY AUTHORIZED DEALERS ARE REQUESTED TO SUBMIT OFFERS. AUTHORIZATION LETTER FROM OEM TO BE SUBMITTED ALONG WITH QUOTATION.**

**Delivery Period:** Within 2 to 4 Weeks

**Supply:** Singareni Bhavan, Hyderabad.

To be installed at PPD Conference Hall.

**Payment Terms:** 100% PAYMENT WILL BE MADE AFTER SUPPLY AND INSTALLATION AT SINGARENI BHAVAN, HYDERABAD WITHIN 30 DAYS. PAYMENT WILL BE MADE ONLINE THROUGH RTGS/NETBANKING. YOU HAVE TO PROVIDE YOUR BANK ACCOUNT DETAILS ALONG WITH IFSC CODE.

Few firms are not supplying items/materials. Their offers will not be considered.

**NOTE: FIRMS ARE REQUESTED TO MENTION DELIVERY PERIOD, HSN CODE, GUARANTEE PERIOD, MAKE OF THE ITEM IF ANY, OFFERS WITHOUT ABOVE, WILL NOT BE CONSIDERED FOR FURTHER PROCESS**

**NOTE:**

- I. Submit sealed covers. These covers to be submitted with Enquiry No, date & Address of SCCL and Firms name.  
 Vendors who can supply within 2 to 4 weeks on receiving the Order copy only should participate in the enquiry. HSN CODE TO BE MENTIONED MAKES TO BE MENTIONED.
- A. Offers are invited from vendors located in Hyderabad/Secunderabad vendors only will be considered.
- B. OFFER VALIDITY: Bidder shall keep the offer valid for a period of 4 months from the date of opening of the tenders. The offer with less validity period than stipulated is liable for rejection.
- C. GST (GOODS AND SERVICE TAX) registration certificate to be submitted along with material HSN/SAC CODE. The applicability of GST & other taxes, if any, in % shall be clearly mentioned an extra.
- D. The bidders offered without any GST & other taxes, their landed cost will be arrived by taking maximum GST% quoted by other bidders.

A) GENERAL TERMS AND CONDITIONS

- a. Validity, delivery period, GST, Warranty / Guarantee to be mentioned.
- b. Tenders received after stipulated time and date will not be considered for whatsoever reasons thereof.
- c. Quotation must be on a paper identifying the firm with telephone number etc. They should be clear and free from corrections and erasing.
- d. Rate quoted by you should be valid for 120 days from the date of opening of tenders and no revision of rates will be permitted during the above period.
- e. Rate should be quoted as per the sizes / units / makes / brands asked for otherwise such offers will not be considered.
- f. The quantity shown in the enquiry is not firm and fixed. It may be increased /decreased.
- g. The material is to be supplied as per the tender enquiry and should be delivered at **Singareni Bhavan, Hyderabad**. No transportation charges will be paid separately unless it is mentioned in the offer clearly. Mention whether the offer is Ex-showroom, Ex-work or delivery at our office, Hyderabad
- h. Samples of the items should be submitted in case, they are asked for in the enquiry
- i. Those who are having ready stocks, capable of supply of material as per the enquiry within the stipulated time only need to forward their offer.
- j. M/s SCCL deserves the right to reject any/all the tender (s) or accept any offer or part thereof without giving any reasons. Its decision in this matter will be final and binding on all the tender/(s).
- k. Sealed tenders can be dropped in the tender box in the Company Purchase Office at Hyderabad or can be sent by post / courier before the due date and time. Fax quotations are not accepted
- l. M/s SCCL will not, in any way, be responsible for any postal delay.
- m. Separate cover may be used for each quotation. Quotations of different enquiries put in single cover will not be considered.
- n. YOU HAVE TO SUBMIT YOUR BANK DETAILS FOR RTGS/ONLINE PAYMENTS

**Tax retention clause:**

The supplier shall upload his Tax Invoice in the GSTN as per the provisions of the GST Act i.e., by 10th of the month subsequent to the month in which "Time of Supply" arises.

In respect of orders where the entire order quantity is executed in phased manner through multiple invoices or where staggered payment is made, if the "Tax Invoice" is not uploaded within the time limits prescribed under GST Act, the tax amount will be withheld from the payment made against subsequent Invoice till such time the invoice is uploaded. The final payment is subject to compliance of all formalities under GST by the supplier.

- B) From 01.11.2020 onwards all the vendors whose turnover is more than Rs.10 Crores or above in the financial years 2021-2022, 2022-2023 & 2023-2024 have to submit e-invoice with QR code printed on it. If the turnover is less than Rs.10 Crores than the firm has to declare that we are exempted from e-invoicing requirement. Therefore, the said e-invoicing provisions are not applicable to our company. Towards this, the firm is required to submit undertaking detailed in "ANNEXURE" along with Invoice.
- D) BILLS WILL NOT BE ACCEPTED WITHOUT e-INVOICING IF THE AGGREGATE TURNOVER IN ANY OF THE THREE FINANCIAL YEARS 2021-2022, 2022-2023 & 2023-2024 EXCEEDS Rs.10 CRORES.
- E) Materials or Items to be supplied 2 to 4 weeks after placement of order.
- F) Firms are requested to submit offers with sufficient knowledge of enquired items. If any doubt regarding enquired item, please ask before submitting offers only.
- G) In case the bidder is unable to submit performance reports, a self certification duly signed and stamped by the bidder, indicating Purchase order number, machine serial number, commissioning date and annual working hours and confirming that the equipment/item offered or similar equipment/item of higher specification, supplied to any Govt. sector/ public sector, have performed satisfactorily for a minimum period of 1 year from the date of commissioning of the equipment and there are no warranty/guarantee claims pending, shall be considered. Self certification is not acceptable for the suppliers made to private Firms

**ANNEXURE**

If turnover not exceeds Rs 10 crores, firm has to submit following undertaking along with the bills.

PROFORMA		
Our turnover during the Financial years 2021-2022,2022-2023 & 2023-2024 is less than the Rs.10 crores		
Name:	Designation:	Company Name:
GSTIN	E-invoicing applicability	SEZ Status (Yes/No)
Any loss of ITC or discharge of interest and penalty arising to SCCL due to any misinformation from us, we are liable to reimburse the same to SCCL on the basis of this declaration.		
SIGNATURE OF OWNER WITH STAMP/SEAL.		

**(H) FAX/MAIL QUOTATIONS ARE NOT ACCEPTABLE.**

**DY.GM(E&M)/HYD**

**DGM(PURCHASE)HYD/HOD**



## Elite FHD Pro Series 12X

PeopleLink Elite FHD Pro Series are cameras for boardrooms. The Pant/Tilt and Zoom features that can be controlled with a remote and allow these camera to have a coverage of up to 72.5 degree wide angle. The 12X Optical Zoom and 16X Digital zoom feature helps in capturing every minute detail including the facial expressions and gestures. The auto-brightness feature adjusts the brightness based on the available lighting conditions to ensure better video quality.

### Product Features

- **Full Function USB Interface**  
Full function USB interface, compatibility USB Type C, support audio, support compressed video output, support UVC V1.1-V1.5 protocol.
- **1080P Full HD**  
Apply Panasonic's 1/2.8 inch, 2.07 million effective pixels high quality HD CMOS sensor, can reach maximum 1920 x 1080 high resolution and achieve quality image.
- **Ultra-high Frame Rate**  
The output frame rate up to 60fps in 1080P.
- **72.5° Wide-angle Lens + 16x Digital Zoom**  
Use 72.5° wide-angle high quality lens, support 12x optical zoom, and 16x digital zoom.
- **Low-light**  
High SNR of CMOS sensor combined with 2D and 3D noise reduction algorithm, effectively reduce the noise, even under low illumination conditions, picture can still keep clean and clear. The image signal-to-noise ratio is up to 55dB or more.

## Product Features

- **Remote Control**  
Multiple controlling method, RS232, RS485, network and USB interface support for remote controlling.
- **H.264 Slice/ H.264 SVC Support Support**  
Slice and SVC encoding mode, adapts to video conference of advance USB application.
- **Dual stream (optional)**  
Support two stream output (YUY2, MJPEG, H.264 each of both), reduce the host codec pressure.
- **Multiple interfaces**  
Support HDMI, USB Type C and LAN interface can output HD video at the same time.
- **Three power supply methods**  
Supports USB 5V power supply, 12V power adapter power supply and PoE power supply.

## Product SPECIFICATIONS

Video System	: 1080P60, 1080P50, 1080P30, 1080P25, 720P60, 720P50
Sensor	: 1/2.8", CMOS, Effective Pixel: 2.07M
Scanning Mode	: Progressive
Lens	: f3.5mm - 42.3mm, F1.8 - F2.8
Optical Zoom	: 12X Optical Zoom
Digital Zoom	: 16x Digital Zoom
Horizontal Angle of View	: 72.5° - 6.9°
Vertical Angle of View	: 44.8° - 3.9°
Minimal Illumination	: 0.5 Lux @ (F1.8, AGC ON)
Shutter	: 1/30s - 1/10000s
White Balance	: Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Manual
Backlight Compensation	: Support
Digital Noise Reduction	: 2D&3D Digital Noise Reduction
Video S/N	: ≥55dB
Horizontal Rotation Range	: ±170°
Vertical Rotation Range	: -30° - +90°
Pan Speed Range	: 2.7° - 35.7°/s
Tilt Speed Range	: 2.7° - 31.5°/s



## PeopleLink Elite FHD Pro Series 12X

### Camera :

H & V Flip	:	Support
Image Freeze	:	Support
Number of Preset	:	255
Preset Accuracy	:	0.1°

### USB Featured

Operate System	:	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color System /	:	YUV / H.264 / MJPEG YUY2 (ISOC): max to 1080P@60fps H.264 AVC: max to 1080P@60fps
Video Format	:	H.264 SVC(optional): max to 1080P@60fps MJPEG: max to 1080P@60fps
Audio on USB	:	Support
USB Video Communication Protocol	:	UVC 1.1-1.5
UVC PTZ	:	Support

### Network Features

Video Compression	:	H.264/MJPEG
Video Stream	:	Main Stream, Sub Stream
Main Stream Resolution	:	1920x1080,1280x720,1024x576,960x540,640x480,640x360
Sub Stream Resolution	:	1280x720,1024x576,720x480,720x408,640x360,320x240, 320x180
Video Bit Rate	:	32Kbps ~ 102400Kbps
Bit Rate Type	:	Variable Rate, Fixed Rate
Frame Rate	:	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Audio Compression	:	AAC
Audio Bit Rate	:	96Kbps, 128Kbps, 256Kbps
Support protocols	:	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.

### Input/Output Interface

USB interface	:	1xUSB Type-C jack
HD Output	:	1xHDMI
Network Interface	:	1xRJ45: 10M/100M Ethernet Interface

## PeopleLink Elite FHD Pro Series 12X

### Input/Output Interface

<b>Audio Interface</b>	:	1xLine In, 3.5mm Audio Interface
<b>Communication Interface</b>	:	1xRS232 In; 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-DiPelco-P 1xRS485, 2pin Phoenix Port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-P
<b>Power</b>	:	JEITA type (DC IN 12V) / Type C

### Generic Specification

<b>Input Voltage</b>	:	DC 12V
<b>Current Consumption</b>	:	12V 1.0A(MAX)/5V 1.5A(MAX)
<b>Operating Temperature</b>	:	0°C – 45°C
<b>Storage Temperature</b>	:	-40°C – 60°C
<b>Power Consumption</b>	:	12W (MAX)
<b>MTBF</b>	:	>30000 hours
<b>Size</b>	:	144mm x 144mm x 167.9mm
<b>Net Weight</b>	:	1.28KG

### PACKAGING INFORMATION

Ordering Information:

Elite FHD Pro Series 12X: PPU-PVC-EPS-12X-16DX

#### GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,  
Madhapur, Hyderabad - 500 081 (India)  
Phone: +91 (40) 66903959 / 60  
Email: vc@peoplelinkvc.com

#### INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070  
UK : +44-20-35190197

Africa : +27-10-5001977  
Australia : +61-29-0988367

Canada : +1-647-4964195  
Middle East : +973-1-6199342

Follow us



[www.peoplelinkvc.com/serial](http://www.peoplelinkvc.com/serial)

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd. All rights reserved. All trademarks are the property of their respective owners. Product images are for illustration purposes only. Actual product may vary due to product enhancements. All specifications are subject to change without notice and are not binding.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | 800002075660901733 | 2015 Confidential Company

[www.peoplelinkvc.com](http://www.peoplelinkvc.com)

 **PeopleLink**



USB and Bluetooth® Speakerphone

# YVC-330



## SEAMLESS COLLABORATION IN OPEN WORKSPACES

The YVC-330 USB & Bluetooth® speakerphone solves the problem of finding vacant rooms for spontaneous meetings. The innovative SoundCap technology converts the audio of open workspaces into a clear and natural signal that is almost as good as being in a quiet meeting room. By focusing on participants around the table and eliminating background noise from noisy working environments it allows participants at the other end of the call to focus on the conversation. Don't be fooled by this portable conference phone's compact design: with Yamaha technology, great sound comes in small packages!

### Key Customer Benefits

- Comfortable remote collaboration anywhere in the office, from open workspaces to conference rooms
- With various expandability and connectivity, you can use it in any remote conference situation as you wish

### Main Use Cases

- **Open Workspace**  
A comfortable meeting in a noisy environment.
- **Small-Medium Conference Room**  
Supports various meetings from small to medium rooms by connecting two units.



### Key Features

- SoundCap technology allows for comfortable remote conversations no matter the environment
  - “Far Field Noise Reduction” picks up your conversations while reducing the distracting noise around you
  - “Self-silence” mutes microphone automatically while meeting participants are not speaking
  - “Self-volume balancer” automatically adjusts speaker volume properly to fit surrounding ambient noise levels
- Small, lightweight design powered by USB brings portability to the office
- Equipped with multiple, market-leading audio processing technologies to achieve enhanced communication
  - High-performance adaptive echo canceller and dereverberation for clear conversations
  - Automatically measures the surrounding environment to optimize acoustic settings
  - High-quality sound collection with speaker tracking function and automatic gain control using three “high-performance” microphones
- 3 unidirectional microphones with human voice activity detection clearly picks up speech, not noise
- Convenient, USB-powered, rich speaker volume and super wide band audio enable stress-free communication
- Ability to daisy chain 2 units for medium-sized spaces
- “Plug-and-play” connectivity with driver-less USB, Bluetooth, NFC and audio in/out connection interfaces allow options for true flexibility
- Compatible with any UC applications
- Sophisticated product design blends into any conference space
- Simple and intuitive user interface





## Technical Specifications

General	Interfaces	USB 2.0 Full Speed (Mini-B), Bluetooth, NFC (Near Field Communication), ERT IN/OUT (stereo mini plug)
	Connectable Devices	USB: Computer running Windows or macOS Bluetooth: Smartphone running Android or iOS
	Power Sources	USB bus power
	Maximum Power Consumption	3.5W
	Dimensions (W x H x D)	235 x 48 x 226 mm (9.3 x 1.8 x 8.9 in)
	Weight	0.8 kg (1.8 lbs)
	Color	Black
	Supported OS	Windows 10 (32bit/64bit), Windows 8.1 (32bit/64bit), Windows 7 (32bit/64bit), macOS 10.14, macOS 10.13, macOS 10.12 USB: USB 2.0 or later
	Bluetooth	Version: 2.1 + EDR Supported profiles: HFP (SBC), A2DP Supported codec: CVSD, SBC, mSBC Wireless output: Class2 Maximum communication distance: 10 m (32.8 ft) (no obstacles) Radio frequency (operational frequency): 2,402 to 2,480 MHz Maximum output power (EIRP): 4.0 dBm (2.5 mW)
	NFC	Compatible devices: NFC-compatible Android devices, versions 5.0, 4.4, 4.3, 4.2, and 4.1
	Accessories	USB cable 3 m (9.8 ft), User's Manual
	Operating Environment	Temperature: 0 to 40 °C (32 to 104 °F) Humidity: 20 to 85% (no condensation)
	Storage Environment	Temperature: -20 to +60 °C (-4 to 132 °F) Humidity: 10 to 90% (no condensation)
	Others	Firmware update (transferred from a PC through USB)
Audio	Microphone	Unidirectional microphones x 3, 360° coverage
	Speaker	Full-range speaker x 1
	Volume	Momentary maximum, 91 dB (0.5 m)
	Frequency Bandwidth	For sound pickup: 100 Hz to 20,000 Hz For playback: 180 Hz to 20,000 Hz
	Signal Processing	Adaptive echo canceller, Noise reduction, Automatic tracking, Automatic gain control, Dereverberation, SoundCap
	Mode	Standard Mode: Pick-up the sound in Small-Medium conference rooms SoundCap Mode: Automatically mute distracting noise in open workspace and deliver only the sound from the pick-up range (radius of 1 m) * 2 units daisy chain connection is available on Standard Mode
Compliance	Safety	CB/G (IEC60065, IEC62368) CE (EN62368, EN62479, EN62311) CCC (GB6688)
	EMC	FCC (part15B ICES-003) CE (EN55032, EN55035, EN55030, EN61000, EN301489) AS/NZS (AS/NZS CISPR32, AS/NZS 4388) KC (KC301489, KC32, KC35) CCC (GB/T 13887, GB19288) VCCI (VCCI 32-1) EAC
	Radio	FCC (Part15B) Class A, ICES-003 CE (EN300328, EN300330) SRRC KC (KC301489)
	RoHS	CE (EN50581)
Warranty	2 years	
Option Accessory	Daisy chain cable (Product number: YCB1-DC1M, Cable length: 3 m, Terminal shape: stereo mini plug x 2 - stereo mini plug x 2)	

### Image of microphone pick-up range

SoundCap OFF



SoundCap ON



\* The sound pickup range depends on the operating environment.

YAMAHA CORPORATION

<https://uc.yamaha.com/yvc-330/>

© 2019 Yamaha Corporation. All rights reserved.

Product features and specifications are subject to change without notice by Yamaha.

All other product and company names and logos that appear in this leaflet are trademarks or registered trademarks of their respective owners.

06-YVC-330-20191024-EN